

SLM G5 Performer

A Compact and Smokeproof Projector for Rental & Staging Applications



The Barco SLM G5 provides a compact, multi-purpose solution for any event. Its sleek black chassis is equipped with a 3-chip Digital Light Processing™ (DLP™) subsystem, which features XGA resolution Digital Micro Mirror Devices™ and a state-of-the-art optical system. With its 5000 ANSI lumen light output, the G5 is ideally suited for mid-range applications and an excellent choice for the demanding environments of rental & staging events.

The Performer

Compact, powerful and able to fulfill a multitude of purposes, Barco's SLM Performer series is the ideal solution for any midrange event.

The versatile SLM G5 has a rugged, sensible design and a light output of 5000 ANSI lumen, making it ideally suited to any application that requires a state-of-the-art projector.

Fast, Easy, Modular ...

With a modular structure which allows greater accessibility to serviceable parts, interlocking design for direct stacking and hanging and an integrated, no-fuss rigging system, the SLM Performer series offers you an efficient, reliable product on which you can depend - time and time again.

BARCO

Visibly yours

Technical specifications

Light Output	5.000 ANSI lumens
Resolution	1024 x 786 (native) 1600 x 1200 (max)
Digital MicroMirror Device™	3 high resolution XGA DMD's
Brightness uniformity	> 90% for the total screen area
Contrast	500:1 (full white/full black) 500:1 (full white/full black)
Lamp	Lifetime (max): 1500 Hrs Lifetime (typ): 1000 Hrs Lamp Power: 1,2 kW
Noise level (@ 20°C - 68°F)	< 43
Noise level (@ 40°C - 104°F)	< 50
Mains Voltage	110/230 V
Power consumption	1.600 W
Ambient Temperature	40°C (104F) max
Size	875 mm x 585 mm x 429 mm 34,5" x 23" x 16,9"
Weight (including rigging gear)	56 kg / 124 lbs
Lenses	BARCO's "click-and-play" TLD lenses provide the highest quality picture. Available both in fixed and zoom versions.
Lens Shift	Motorized V shift: up to 118 % Motorized H shift: up to 65 %
Sealed DLP™ core	Yes
Seamless Switching	Standard
ScenergiX	Standard
Fixed Inputs	<ul style="list-style-type: none"> • 2 Multifunctional 5-cable inputs for the connection of RGB analogue signals with standard sync (BNC connectors) or tri-level sync, sync on green or separate sync, Standard Video signals, S-VHS signals • 2 Multistandard DVI • SDI input (Serial Digital Input)
Optional Inputs	One free digital input slot for optional input modules: <ul style="list-style-type: none"> • SDI • HD - SDI
Remote Control	<ul style="list-style-type: none"> • RS232 or RS422 loop-through input (D9-connector) for PC based projector control • Communication input (D9-connector) for peripherals • 3 pin male XLR connector for wired remote (standard remote) • 3 pin female XLR connector for bi-directional communication (rugged remote)